

RBH fingerprint + MiFARE DESFire card reader now compatible with RBH's NFC & Bluetooth mobile credentials

## **RBH-BFR-150-DNB SERIES**

RBH's best-selling BFR-150 fingerprint reader has been updated to read RBH's award winning UHSC NFC & Bluetooth mobile credentials.

Users will benefit from its unparalleled performance, ease-of-use, precision and fast matching speed and the trusted and innovative technology of blueLINE.



OSDP V1&V2

Compact design

+9.500 fingerprint templates

Fast matching speed

NFC & Bluetooth (BLE) mobile credential compatible

Fully integrated with







With the technology of



Specifications	
Verification option	Fingerprint / Fingerprint + Card / Card
Verification mode	1:1 / 1:N
Verification time	Less Than 2.0 Seconds (1:1 Verification Mode)
Registration Time	Less Than 3.0 Seconds
Templates	Up to 9,500
Technology	DESFire (EV1 & EV2) / Bluetooth / NFC
Integrated Reader	SECTOR / CSN for MiFARE Classic / Plus / DESFire EV1/2/3 (RBH-BFR-150-D for sector & RBH-BFR-150-S for CSN)
PC to Reader / Panel to Reader	Ethernet TCP / IP Cable / Wiegand (6 Cond. Shielded, Stranded, 18-22 AWG)
Communication data	
Communication method	TCP/IP, Weigand, OSDP ver. 1 & 2
Communication environment	LAN / WAN
Ethernet Interface	10/100M Base-T, Auto Crossover
Wiegand Out	1
Indication data & User interface	
Buzzer	Single Tone
Anti-Tampering switch	Yes
Electrical data conditions	
Operation voltage	DC 9~24 V, 1A
Operation temperature	0°C to 55°C (32°F to 131°F)
Operation humidity	5% - 95% RH
Rating	IP-54
Physical data	
Dimensions	160 x 57 x 40 mm - (6.2 x 2.2 x 1.5 in)
Weight	0.3 lb (180 gr)
Certifications	<b>F</b> € <b>©</b>

## Order:

RBH-BFR-150-D for sector RBH-BFR-150-S for CSN





RBH Access Technologies, Inc. 2 Automatic Road, Suite 108 Brampton ON L6S 6K8, Canada

> 1-905-790-1515 1-905-790-3680

info@rbh-access.com





